








Note: Les composants identifiés par un trame et une marque Δ sont critiques pour la sécurité. Ne les remplacer que par une pièce portant le numéro spécifié.

Les composants identifiés par un tramé et une marque  sont critiques pour la sécurité. Ne les remplacer que par une pièce portant le numéro spécifié.

Note: The components identified by shading and mark **A** are critical for safety. Replace only with part number specified.

Note:

- All capacitors are in μF unless otherwise noted, $\text{pF} = 10^{-12}\text{F}$, 500W or less are not indicated except for electrolytics.
- All resistors are in ohms, $\frac{1}{2}\text{W}$ unless otherwise noted. $\text{k}\Omega = 1000\Omega$, $\text{M}\Omega = 1000\text{k}\Omega$
- All variable and adjustable resistors have characteristic curve B, unless otherwise noted.
-  : nonflammable resistor.
-  : fusible resistor.
-  : B + bus.
-  : panel designation.
-  : adjustment for repair.
-  : B — bus.
- Voltages are dc with respect to ground unless otherwise noted.

- Readings are taken under no signal conditions with a VOM (20k Ω /V).
- []: AEP, UK model
- < >: US, Canadian model
- no mark: common
- Voltage variations may be noted due to normal production tolerances.
- **Switch**

Ref. No.	Switch	Position
S101	POWER	OFF

